Datasheet

Guardian 5in1 Adhesive and Wall Mount Antenna

Part No:
MA952.A.LBIVW.001

Description:

Guardian 5in1 Adhesive and Wall Mount Antenna 4*LTE GNSS Antenna

Features:

Low-profile Housing – Mounts flush to Wall

4* LTE MIMO 617-960MHz / 1400-1500MHz/ 1710-2170MHz /
2490-2690MHz / 3300-3600MHz / 5150-5925MHz

1* GPS-GLONASS-GALILEO-BeiDou Antenna

1* Satellite L Band Antenna

Worldwide 4G Bands including fallback to 3G & 2G

IP67 Waterproof ASA Enclosure

Dims: 146*134*20mm

1M Low Loss KSR200-P and RG-174 Cables with SMA(M) connectors

Cables and Connectors Customizable

RoHS & Reach Compliant

1.	Introduction	3
2.	Specifications	4
3.	Active Antenna Characteristics	8
4.	Antenna Characteristics	15
5.	Radiation Patterns	19
6.	Mechanical Drawing	34
7.	Packaging	35
	Changelog	36

Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

Copyright © Taoglas Ltd.

1. Introduction

The MA952 Guardian is a next generation combination antenna. It is the first panel antenna worldwide designed for IoT Gateway and Router devices with multiple wireless technologies. It is a low profile 5in1 wall and adhesive mount antenna. It is a heavy-duty, fully IP67 waterproof external M2M antenna for use by RF professionals in:

-IoT Gateway and Routers
-HD Video Streaming
-Transportation

This antenna delivers powerful MIMO antenna technology for Sub-6GHz at (2G/3G/4G) bands worldwide for access points, terminals and routers. This also includes CAT-M1 and NB-IoT and the recently introduced 600MHz Extended LTE Band 71. It also supports GPS-GLONASS-GALILEO-BEIDOU for location accuracy. It enables designers to cover a wide range of technologies by installing a single antenna.

4G wireless applications demand high speed data uplink and downlink. High efficiency and high gain MIMO antennas are necessary to achieve the required signal to noise ratio and throughput required to solve these challenges. Taoglas also takes care to have high isolation among these antennas to prevent self-interference. Low loss cables used to keep efficiency high over long cable lengths.

The GPS-GLONASS-GALILEO-BEIDOU active antenna has been carefully designed for excellent performance across all L1 GNSS bands, leading to higher location accuracy and stability of tracking in urban environments.

The housing is IP67 waterproof and comes with a 3M adhesive. The antenna can be mounted internally or externally on a vehicle. The MA952 comes with 1meter, low loss KSR200-P coaxial cables for the LTE antennas, and RG-174 coaxial cable for the GNSS antenna as standard. Customized cables and connector versions are also available.

2. Specifications

GNSS Frequency Band							
GPS/QZSS	L1 1575.42MHz	L2 1227.6MHz	L5 1176.45MHz	L6 1278.75MHz			
	■	□	□	□			
GLONASS	L5R 1176.45MHz	L3PT 1201.5MHz	L2PT 1246MHz	L1CR 1575.42MHz	L1PT 1602MHz		
	□	□	□	■	■		
Galileo	E5a 1176.45MHz	E5b 1201.5MHz	E4 1215MHz	E3 1256MHz	E6 1278.75MHz	E2 1561MHz	L1 1575.42MHz
	□	□	□	□	□	■	■
Beidou	B1 1561MHz	B2 1207.14MHz	B3 1268.52MHz				
	■	□	□				
Compass	E5B(B2)/ E6(B3) 1268.56MHz	E2(B1) 1561MHz					
	□	■					
SBAS	Omnistar 1542.5MHz	WAAS/EGN OS 1575.42MHz					
	□	■					

GNSS ELECTRICAL			
Frequency (MHz)	1561	1575.42	1602
VSWR (max.)	2.0:1	2.0:1	2.0:1
Passive Antenna Efficiency (%) (Without cable loss)	63	48	57
Passive Antenna Gain at Zenith (dBi) (Without cable loss)	3	1.98	3.01
Axial Ratio (dB)	<9.7	<14.2	<5.9
Polarization	RHCP		
Impedance	50Ω		
Cable	RG174, 1meter standard, fully customizable		
Connector	SMA(M) standard, fully customizable		

LNA and Filter Electrical Properties			
Frequency (MHz)	1561	1575.42	1602
VSWR (max.)	2.0:1	2.0:1	2.0:1
Gain@1.8V (Typ.)	28 dB	28 dB	28 dB
Gain@3.0V (Typ.)	30 dB	30 dB	30 dB
Gain@5.5V (Typ.)	33 dB	33 dB	33 dB
Noise@1.8V (Typ.)	1.13 dB	1.13 dB	1.13 dB
Noise@3.0V (Typ.)	1.13 dB	1.13 dB	1.13 dB
Noise@5.5V (Typ.)	1.14 dB	1.14 dB	1.14 dB
Power consumption@1.8V (Typ.)	7.9 mA		
Power consumption@3.0V (Typ.)	9.0 mA		
Power consumption@5.5V (Typ.)	9.9 mA		
Total Specification (Through Antenna, SAW Filter and LNA)			
Frequency (MHz)	1561	1575.42	1602
Gain@3V (dBi)	28 ± 3	28 ± 3	28 ± 3
Output Impedance	50 Ω		

LTE Antenna											
Frequency (MHz)		5G NR Band 71	LTE700	GSM850/ 900	5G NR Band 74, 75, 76	DCS	PCS	UMTS1	LTE2600	5G NR Band 77, 78, 79	LTE5200/ WiFi5800
		617 ~698	698 ~806	824 ~960	1427 ~1518	1710 ~1880	1850 ~1990	1920 ~2170	2490 ~2690	3300 ~3500	5150 ~5925
Efficiency (%)											
MIMO 1	0.3m	40.44	51.83	66.88	75.51	86.58	81.66	77.92	82.62	67.29	57.81
MIMO 2	0.3m	48.83	67.43	69.89	61.17	67.25	61.40	57.75	58.64	58.68	58.41
MIMO 3	0.3m	56.78	63.10	67.82	58.58	64.22	63.44	62.80	74.19	66.34	60.93
MIMO 4	0.3m	43.36	43.73	46.25	66.04	85.59	81.34	75.60	77.25	63.00	50.68
Average Gain (dB)											
MIMO 1	0.3m	-3.93	-2.85	-1.75	-1.22	-0.63	-0.88	-1.08	-0.83	-1.72	-2.38
MIMO 2	0.3m	-3.11	-1.71	-1.56	-2.13	-1.72	-2.12	-2.38	-2.32	-2.32	-2.34
MIMO 3	0.3m	-2.46	-2.00	-1.69	-2.32	-1.92	-1.98	-2.02	-1.30	-1.78	-2.15
MIMO 4	0.3m	-3.63	-3.59	-3.35	-1.80	-0.68	-0.90	-1.21	-1.12	-2.01	-2.95
Peak Gain (dBi)											
MIMO 1	0.3m	2.32	2.18	4.56	4.44	4.95	4.71	4.71	4.77	4.96	3.84
MIMO 2	0.3m	2.49	3.66	4.28	4.72	4.46	4.46	5.58	6.46	3.97	4.32
MIMO 3	0.3m	2.83	3.11	3.76	4.42	6.11	6.11	5.82	5.49	4.78	4.79
MIMO 4	0.3m	1.98	1.39	4.07	4.82	4.51	4.48	4.39	4.37	4.57	5.06
Impedance		50Ω									
Polarization		Linear									
Radiation Pattern		Omni									
Max. input power		1 W									

Mechanical	
Height	20 ±2 mm
Planner Dimension	146*134 mm
Casing	ASA
Cable	KSR200-P, 1000 mm for LTE RG-174 1000 mm for GNSS
Connector	SMA(M)
Weight	450g
Environmental	
Protection	IP67
Temperature Range	-40°C to 85°C
Humidity	Non-condensing 65°C 95% RH

3. Active Antenna Characteristics

3.1 Block Diagram (Active antenna)



3.2 Passive Antenna Return Loss



3.3 Passive Antenna Efficiency



3.4 Passive Antenna Average Gain



3.5 Passive Antenna Peak Gain



3.6 Passive Antenna Axial Ratio (Zenith is at 0°)



1561MHz



1575.42MHz



1602MHz

3.7 Active measurements

LNA Gain @ 3.0V



Noise Figure @ 3.0V



3.8 Passive Antenna 2D Radiation Patterns

XY Plane



XY Plane



XY Plane



3.9 Passive Antenna 3D Radiation patterns



1561MHz



1575.42MHz



1602MHz

4. Antenna Characteristics

4.1 Test Setup



Free space

4.2 Return Loss



4.3 Isolation



4.4 Efficiency



4.5 Average gain



4.6 Peak gain


10
5
0
-5
-10
(dBi)
500
1000
1500
2000
2500
3000
3500
4000
4500
5000
5500
6000
(MHz)
LTE1
LTE2
LTE3
LTE4

5. Radiation Patterns

5.1 Test Setup



Free space

5.2 2D Radiation Patterns

5.2.1 LTE MIMO1

XY Plane











XZ Plane











YZ Plane











5.2.1 LTE MIMO2

XY Plane











XZ Plane











YZ Plane











5.2.3 LTE MIMO3

XY Plane











XZ Plane











YZ Plane











5.2.4 LTE MIMO4

XY Plane











XZ Plane











YZ Plane











5.3 3D Radiation Pattern

5.3.1 LTE MIMO1


















TOTAL POWER 2500 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 2690 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 3300 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 3400 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 5150 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 5550 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 5925 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB

5.3.2 LTE MIMO2


















TOTAL POWER 2500 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB
+z


TOTAL POWER 2690 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB
+z


TOTAL POWER 3300 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB
+z


TOTAL POWER 3400 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB
+z


TOTAL POWER 5150 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB
+z


TOTAL POWER 5550 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB
+z


TOTAL POWER 5925 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB
+z

5.3.3 LTE MIMO3


















TOTAL POWER 2500 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 2690 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 3300 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 3400 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 5150 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 5550 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 5925 MHz
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB

5.3.4 LTE MIMO4


















TOTAL POWER 2500 MHz
+y
+x
+z
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 2690 MHz
+y
+x
+z
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 3300 MHz
+y
+x
+z
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 3400 MHz
+y
+x
+z
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 5150 MHz
+y
+x
+z
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 5550 MHz
+y
+x
+z
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB


TOTAL POWER 5925 MHz
+y
+x
+z
+10
+5
0
-5
-10
-15
-20
-25
-30
-35
-40
dB

6. Mechanical Drawing (Units: mm)



	Name	P/N	Material	Finish	QTY
1	Top Housing	000116B000000A	ASA	Black	1
2	Bottom Housing	000116B010000A	ASA	Black	1
3	Rubber-3 Holes	000715G000000A	Silicone Rubber	Black	1
4	Clear Label	001015H040000A	PET	Transparent	1
5	Heat Shrink Tube (LTE-1)	001317C020000A	PE	Red Tube/White Text	1
6	Heat Shrink Tube (LTE-2)	001317C030000A	PE	Red Tube/White Text	1
7	Heat Shrink Tube (LTE-3)	001317J000000A	PE	Red Tube/White Text	1
8	Heat Shrink Tube (LTE-4)	001317J010000A	PE	Red Tube/White Text	1
9	Heat Shrink Tube (GNSS)	001316C000000A	PE	Blue Tube/White Text	
10	Empty Label(48*30)	001015G000000A	PEPA	White	1
11	Barcode Label(25*9)	001015G010000A	PET	White	1
12	RG174 Coaxial Cable	301315C000000A	PVC	Black	1
13	KSR-200-P Coaxial Cable	305416B000000A	PE	Black	4
14	SMA(M)ST (For RG174)	200216B00005BA	Brass	Au Plated	1
15	SMA(M)ST (For KSR200)	200215K00004BA	Brass	Au Plated	4
16	Double Sided Adhesive(White Foam)	001019B000000A	3M GT7130 3t	Translucent Red Liner	1
17	Rubber-2 Holes	000715H010000A	Silicone Rubber	Black	1

7. Packaging



1 No. MA952.A.LBIVW.001 per small box
Box Dimensions - 260*235*105mm
Weight - 0.71Kg



1 Outer Carton
Carton Dimensions - 540*490*240mm
8 pcs MA952.A.LBIVW.001 per carton
Weight - 6.3Kg



Pallet Dimensions 1200*1000*1400mm
20 Cartons per Pallet
4 Cartons per layer
5 Layers



Changelog for the datasheet

SPE-19-8-054 – MA952.A.LBIVW.001

Revision: A (Original First Release)	
Date:	2019-04-19
Notes:	
Author:	Jack Conroy

Previous Revisions

TAOGLAS®

www.taoglas.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taoglas:
MA952.A.LBIVW.001